

RAVENOL Super Low Emission Truck 15W-40

SAE: 15W-40

Mineral



20 L

Vendor:
1123216-020

20 L, ecobox

Vendor:
1123216-B20



60 L

Vendor:
1123216-060



208 L

Vendor:
1123216-208

RAVENOL Super Low Emission Truck SAE 15W-40 is an all-year engine oil for diesel engines with or without turbo charging, for trucks, busses and work machines.

RAVENOL Super Low Emission Truck SAE 15W-40 is a diesel engine oil with high wear protection, which is also suitable for vehicles with exhaust gas recirculation systems.

RAVENOL Super Low Emission Truck SAE 15W-40 is specially designed for extended oil change intervals (under consideration of the manufacturer instruction).

Characteristics

- **RAVENOL Super Low Emission Truck SAE 15W-40** offers:
 - High pressure absorption capacity
 - High oxidation stability
 - Outstanding temperature stability
 - Very good detergent and dispersing properties
 - Excellent aging resistance

- High wear protection
- Excellent viscosity-temperature behavior
- Neutrality to seals
- High safety reserves even with boundary lubrication conditions
- Best suitability for difficult operating conditions

Characteristics

Title	Value	Audit
API	CK-4, SN	
ACEA	E7, E9	
JASO	DH-2	
Հաստատված է արտադրողի կողմից	DTFR 15C100 (MB 228.31), Mack EOS-4.5, Renault RLD-3, Volvo VDS-4.5	
Համապատասխանում է արտադրողի պահանջներին	Caterpillar ECF-3, Cummins CES 20081, Cummins CES 20086, DDC 93K218, DDC 93K222, Deutz DQC III-10 LA, MAN M 3275, MAN M 3575, MB 228.31, MTU Type 2.1	
Համապատասխանում է արտադրողի բնութագրերին	ACEA E11	
Suitable for	IVECO	
Density at 20 °C	866 kg/m ³	EN ISO 12185
Գույն	reddish brown	տեսողական
Մածուցիկություն 100 °C-ում	15.6 mm ² /s	DIN 51562-1
Մածուցիկություն 40 °C-ում	116.1 mm ² /s	DIN 51562-1
Viscosity Index VI	142	DIN ISO 2909
CCS Viscosity at -20 °C	5.370 mPa*s	ASTM D5293
Low Temp. Pumping viscosity (MRV) at -40 °C	18.400 mPa*s	ASTM D4684
Pourpoint	-39 °C	DIN ISO 3016
Անկայունություն NOACK	7.8 % M/M	ASTM D5800
Flashpoint	240 °C	DIN EN ISO 2592
TBN	11 mgKOH/g	ASTM D2896
Sulphated Ash	1 %wt.	DIN 51575

Out of production

Product	Vendor	Barcode
20 l	1123216-020-01-999	
208 l	1123216-208-01-999	