

# RAVENOL Standard Truck 30

**SAE: 30W****Mineral****20 l**Vendor:  
**1123620-020****20 l, ecobox**Vendor:  
**1123620-B20****60 l**Vendor:  
**1123620-060****208 l**Vendor:  
**1123620-208****1 000 l**Vendor:  
**1123620-700**

**RAVENOL Standard Truck SAE 30** is mineral mono grade motor oil for trucks. It is an all-season oil for all truck diesel engine types.

**RAVENOL Standard Truck SAE 30** offers high protection against friction and abrasion, excellent cold start characteristics. Extended oil change intervals according to manufacturer's recommendations.

## Application Note

**RAVENOL Standard Truck SAE 30** is mono grade motor oil for use in truck diesel engines. It is also suitable for stationary plants.

## **Characteristics**

- Good shear stability
- High oxidation stability
- Excellent viscosity temperature behaviour
- Convincing detergent and dispersant characteristics
- High safety reserves
- Good cold start characteristics
- Best corrosion protection
- Suitable for catalysts

## Characteristics

Title	Value	Audit
API	CF, SF	
Համապատասխանում է արտադրողի պահանջներին	Allison C-4, Caterpillar TO-2, MAN 270, MB 227.0, MIL-L-2104 E, MTU Type 1, Voith DIWA, Voith Retarder A, ZF TE-ML 02C, ZF TE-ML 03B, ZF TE-ML 04B, ZF TE-ML 06A, ZF TE-ML 07D	
Density at 20 °C	887 kg/m <sup>3</sup>	EN ISO 12185
Գույն	tan	տեսողական
Մածուցիկություն 100 °C-ում	11.6 mm <sup>2</sup> /s	DIN 51562-1
Մածուցիկություն 40 °C-ում	102.3 mm <sup>2</sup> /s	DIN 51562-1
Viscosity Index VI	100	DIN ISO 2909
Pourpoint	-27 °C	DIN ISO 3016
Flashpoint	262 °C	DIN EN ISO 2592
TBN	13 mgKOH/g	ASTM D2896

## Out of production

Product	Vendor	Barcode
20 l	1123620-020-01-999	
60 l	1123620-060-01-999	
208 l	1123620-208-01-999	