

RAVENOL Super Truck 10W

SAE: 10W**Mineral****20 l**Vendor:
1123710-020**20 l, ecobox**Vendor:
1123710-B20**60 l**Vendor:
1123710-060**208 l**Vendor:
1123710-208**1 000 l**Vendor:
1123710-700

RAVENOL Super Truck SAE 10W is high alloyed HD engine oil with synthetic additives. It is suitable for diesel engines of trucks even with turbo charging. The high additive content guarantees an excellent effect regarding detergent, dispersant and anticorrosion characteristics.

RAVENOL Super Truck SAE 10W is a top-quality product with high safety reserves.

Application Note

RAVENOL Super Truck SAE 10W is mono grade motor oil for use in truck diesel engines with or without turbo charger.

Characteristics

- High oxidation stability
- Excellent viscosity temperature behaviour
- Convincing detergent and dispersant characteristics
- High safety reserves
- Good cold start characteristics
- Best corrosion protection
- Suitable for catalysts
- Reduced emissions

Characteristics

Title	Value	Audit
API	CF-4	
ACEA	B4, E2	
Համապատասխանում է արտադրողի պահանջներին	MAN 270, MB 228.0, MTU Type 1, Voith DIWA	
Density at 20 °C	864 kg/m ³	EN ISO 12185
Գույն	Brown	տեսողական
Մածուցիկություն 100 °C-ում	6.9 mm ² /s	DIN 51562-1
Մածուցիկություն 40 °C-ում	42.4 mm ² /s	DIN 51562-1
Viscosity Index VI	122	DIN ISO 2909
Pourpoint	-39 °C	DIN ISO 3016
Flashpoint	234 °C	DIN EN ISO 2592

Out of production

Product	Vendor	Barcode
20 l	1123710-020-01-999	
208 l	1123710-208-01-999	