

RAVENOL Super Truck 40

SAE: 40W**Mineral****1 l**Vendor:
1123725-001**5 l**Vendor:
1123725-005**10 l**Vendor:
1123725-010**20 l**Vendor:
1123725-020**20 l, ecobox**Vendor:
1123725-B20**60 l**Vendor:
1123725-060**208 l**Vendor:
1123725-208**1 000 l**Vendor:
1123725-700

RAVENOL Super Truck SAE 40 is high alloyed HD engine oil with synthetic additives. It is suitable for diesel engines of trucks even with turbo charging. The high additive content guarantees an excellent effect regarding detergent, dispersant and anticorrosion characteristics.

RAVENOL Super Truck SAE 40 is a top-quality product with high safety reserves.

Application Note

RAVENOL Super Truck SAE 40 is mono grade motor oil for use in truck diesel engines with or without turbo charger.

Please follow engine manufacturer's recommendations.

Characteristics

- High oxidation stability
- Excellent viscosity temperature behaviour
- Convincing detergent and dispersant characteristics
- Good cold start characteristics
- Best corrosion protection
- High safety reserves even with boundary lubrication conditions
- Suitable for catalysts

Characteristics

Title	Value	Audit
API	CF-4, SG	
ACEA	B4, E2	
Համապատասխանում է արտադրողի պահանջներին	Allison C-4, Caterpillar TO-2, Deutz DQC I-02, MAN 270, MB 228.0, MB 235.12, MIL-L-2104 D, MTU Type 1, ZF TE-ML 02H, ZF TE-ML 04A, ZF TE-ML 04B	
Density at 20 °C	883 kg/m ³	EN ISO 12185
Գույն	Brown	տեսողական
Մածուցիկություն 100 °C-ում	14.3 mm ² /s	DIN 51562-1
Մածուցիկություն 40 °C-ում	131.5 mm ² /s	DIN 51562-1
Viscosity Index VI	108	DIN ISO 2909
Pourpoint	-21 °C	DIN ISO 3016
Flashpoint	246 °C	DIN EN ISO 2592

Out of production

Product	Vendor	Barcode
1 l	1123725-001-06-999	
5 l	1123725-005-01-400 1123725-005-01-999	
10 l	1123725-010-01-999	
20 l	1123725-020-01-400 1123725-020-01-999	
208 l	1123725-208-01-999	