

# RAVENOL Gasmotorenöl 40

SAE: 40W

Mineral



**20 l**

Vendor:  
**1133105-020**  
Vendor:  
1133105-020-01-999



**20 l, ecobox**

Vendor:  
**1133105-B20**



**60 l**

Vendor:  
**1133105-060**  
Vendor:  
1133105-060-01-999



**208 l**

Vendor:  
**1133105-208**  
Vendor:  
1133105-208-01-999

RAVENOL Gasmotorenöl SAE 40 is gas engine oil suitable for the lubrication of four stroke gas engines, when gases are used with lower sulphur contents.

## Application Note

RAVENOL Gasmotorenöl SAE 40 is suitable to apply in four stroke gas engines for which lower acid neutralisation capacity is required. RAVENOL Gasmotorenöl SAE 40 can be applied when natural gas, biomass gas or sewage gas are used. Application of this motor oil contributes to a longer lifetime and decreased maintenance costs, because longer Service fill times are possible. Due to its lower phosphate content a longer lifetime of the catalyst can be achieved.

## Characteristics

- Reduction of deposits in the combustion chamber and on the valves
- Good noise reducing properties
- Good oxidation resistance

- Strong acid neutralisation capacity
- Excellent cleaning properties
- Good protection against wear
- Excellent filterability

## Characteristics

<i>Title</i>	<i>Value</i>	<i>Audit</i>
Density at 20 °C	872 kg/m <sup>3</sup>	EN ISO 12185
Գույն	Brown	տեսողական
Մածուցիկություն 100 °C-ում	13.7 mm <sup>2</sup> /s	DIN 51562-1
Մածուցիկություն 40 °C-ում	132 mm <sup>2</sup> /s	DIN 51562-1
Viscosity Index VI	108	DIN ISO 2909
Pourpoint	-21 °C	DIN ISO 3016
Flashpoint	274 °C	DIN EN ISO 2592
TBN	5.5 mgKOH/g	ASTM D2896
Engine cycle	4T	