

RAVENOL MARINEOIL DIESEL SHPD 10W-40

SAE: 10W-40*Semi-synthetic***1 l**Vendor:
1162100-001**4 l**Vendor:
1162100-004**10 l**Vendor:
1162100-010**20 l**Vendor:
1162100-020**20 l, ecobox**Vendor:
1162100-B20**60 l**Vendor:
1162100-060**208 l**Vendor:
1162100-208**1 000 l**Vendor:
1162100-700

RAVENOL MARINEOIL DIESEL SHPD 10W-40 is a low friction engine oil for the use in marine diesel engines.

RAVENOL MARINEOIL DIESEL SHPD 10W-40 is produced with unconventional and HC basic oils, synthetic components and modern additives.

RAVENOL MARINEOIL DIESEL SHPD 10W-40 guarantees longest oil change intervals and a high corrosion protection with a low oil and fuel consumption.

Application Note

RAVENOL MARINEOIL DIESEL SHPD 10W-40 is tried and tested for aggregates specifying:

Specifications: API CI-4/CF, ACEA E7, B4

Recommendations: Caterpillar, Detroit Diesel, IVECO, MAN, Mercruiser, MTU, NANNI Diesel, PERKINS, SKL, Steyr, SULZER, VETUS DEUTZ, VOLVO PENTA, Yanmar

Characteristics

- Excellent detergent and dispersant characteristics
- Low evaporation
- High aging stability
- Protection of reflecting surface formation
- Very good cold start characteristics
- Reduces oil and fuel consumption

Characteristics

Title	Value	Audit
API	CF, CI-4	
ACEA	B4, E7	
Համապատասխանում է արտադրողի պահանջներին	DDC Detroit Diesel, Scania LDF-2, VETUS DEUTZ, Volvo PENTA	
Suitable for	Caterpillar, IVECO, MAN, MTU, Mercruiser, NANNI Diesel, PERKINS, SKL, STEYR, SULZER, Yanmar	
Density at 20 °C	866 kg/m ³	EN ISO 12185
Գույն	Blue	տեսողական
Մածուցիկություն 100 °C-ում	13.7 mm ² /s	DIN 51562-1
Մածուցիկություն 40 °C-ում	92 mm ² /s	DIN 51562-1
Viscosity Index VI	151	DIN ISO 2909
CCS Viscosity at -25 °C	6470 mPa*s	ASTM D5293
Pourpoint	-36 °C	DIN ISO 3016
Flashpoint	214 °C	DIN EN ISO 2592
TBN	11 mgKOH/g	ASTM D2896
Sulphated Ash	1.3 %wt.	DIN 51575

Out of production

Product	Vendor	Barcode
1 l	1162100-001-01-999 1162100-001-06-999	
4 l	1162100-004-01-999	
10 l	1162100-010-01-999	
20 l	1162100-020-01-999	
60 l	1162100-060-01-999	
208 l	1162100-208-01-999	