

RAVENOL MARINEOIL PETROL 10W-40

SAE: 10W-40

Semi-synthetic



1 L

Vendor:
1162200-001



4 L

Vendor:
1162200-004



10 L

Vendor:
1162200-010



20 L

Vendor:
1162200-020



20 L, ecobox

Vendor:
1162200-B20



60 L

Vendor:
1162200-060



208 L, տպագիր տակառ

Vendor:
1162200-D60



208 L

Vendor:
1162200-208



1 000 l

Vendor:

1162200-700

RAVENOL MARINEOIL PETROL 10W-40 is an engine oil for the use in marine gasoline engines.

RAVENOL MARINEOIL PETROL 10W-40 is produced with unconventional and HC basic oils, synthetic components and modern additives.

RAVENOL MARINEOIL PETROL 10W-40 guarantees longest oil change intervals and a high corrosion protection with a low oil and fuel consumption.

Application Note

RAVENOL MARINEOIL PETROL 10W-40 is tried and tested for aggregates specifying:

Specifications: API SL

Recommendations: Kohler, Mercruiser, VOLVO Penta AB, Yanmar.

Characteristics

- Excellent detergent and dispersant characteristics
- Low evaporation
- High aging stability
- Protection of reflecting surface formation
- Very good cold start characteristics
- Reduces oil and fuel consumption

Characteristics

Title	Value	Audit
API	SL	
Համապատասխանում է արտադրողի պահանջներին	Volvo Penta AB	
Suitable for	Kohler, Mercruiser, Yanmar	
Density at 20 °C	866 kg/m ³	EN ISO 12185
Գույն	Blue	տեսողական
Մածուցիկություն 100 °C-ում	13.6 mm ² /s	DIN 51562-1
Մածուցիկություն 40 °C-ում	91.8 mm ² /s	DIN 51562-1
Viscosity Index VI	150	DIN ISO 2909
CCS Viscosity at -25 °C	6480 mPa*s	ASTM D5293
Pourpoint	-36 °C	DIN ISO 3016
Flashpoint	210 °C	DIN EN ISO 2592
TBN	11 mgKOH/g	ASTM D2896
Sulphated Ash	1.3 %wt.	DIN 51575

Out of production

Product	Vendor	Barcode
1 l	1162200-001-01-999	
	1162200-001-06-999	
4 l	1162200-004-01-999	
10 l	1162200-010-01-999	
20 l	1162200-020-01-999	
60 l	1162200-060-01-999	
208 l	1162200-208-01-999	