

RAVENOL MARINE 830 30 TBN8

SAE: 30W**Mineral****1 l**

Vendor:
1163001-001
Vendor:
1163001-001-01-999

**4 l**

Vendor:
1163001-004
Vendor:
1163001-004-01-999

**10 l**

Vendor:
1163001-010

**20 l**

Vendor:
1163001-020
Vendor:
1163001-020-01-999

**20 l, ecobox**

Vendor:
1163001-B20

**60 l**

Vendor:
1163001-060
Vendor:
1163001-060-01-999

**208 l**

Vendor:
1163001-208
Vendor:
1163001-208-01-999

**1 000 l**

Vendor:
1163001-700

RAVENOL MARINE 830 SAE 30 TBN8 is a mineral diesel engine oil for the navy.

RAVENOL MARINE 830 SAE 30 TBN8 is produced with a special additivation for the demands for a navy oil for the use in crosshead diesel engines and engines for the coasting and inland navigation.

Application Note

RAVENOL MARINE 830 SAE 30 TBN8 is used as a lubrication oil in slowly running crosshead diesel engines and as an engine oil in easy loaded engines of the coasting and inland navigation.

Characteristics

- a very good oxidation resistance
- a stable viscosity index
- a good neutralizing power to neutralize acid connections which occur when burning diesel fuels
- a good cleaning power
- a good corrosion protection
- a good foam prevention
- a low pourpoint
- a good water separation behaviour

Characteristics

Title	Value	Audit
API	CC	
Համապատասխանում է արտադրողի պահանջներին	DEF 2101D, MIL-L-2104 A	
Համապատասխանում է արտադրողի բնութագրերին	SAE 30	
Density at 20 °C	883 kg/m ³	EN ISO 12185
Գույն	Brown	տեսողական
Մածուցիկություն 100 °C-ում	11.45 mm ² /s	DIN 51562-1
Մածուցիկություն 40 °C-ում	102 mm ² /s	DIN 51562-1
Viscosity Index VI	99	DIN ISO 2909
Pourpoint	-21 °C	DIN ISO 3016
Flashpoint	264 °C	DIN EN ISO 2592
TBN	8.5 mgKOH/g	ASTM D2896
Sulphated Ash	1.15 %wt.	DIN 51575
Engine cycle	4T	

Out of production

Product	Vendor	Barcode
1 l	1163001-001-06-999	
10 l	1163001-010-01-999	