

RAVENOL MARINE 1230 30 TBN12

SAE: 30W**Mineral****1 l**

Vendor:
1163010-001
Vendor:
1163010-001-01-999

**4 l**

Vendor:
1163010-004
Vendor:
1163010-004-01-999

**10 l**

Vendor:
1163010-010

**20 l**

Vendor:
1163010-020
Vendor:
1163010-020-01-999

**20 l, ecobox**

Vendor:
1163010-B20

**60 l**

Vendor:
1163010-060
Vendor:
1163010-060-01-999

**208 l**

Vendor:
1163010-208
Vendor:
1163010-208-01-999

**1 000 l**

Vendor:
1163010-700

RAVENOL MARINE 1230 SAE 30 TBN12 is a mineral diesel engine oil for the navy.

RAVENOL MARINE 1230 SAE 30 TBN12 is made from high quality solvent refined basic oils with a special multi functional additivation for the demands of a navy oil for the use of navy diesel engines and for the lubrication of gear transfers in aggregates used on boats.

Application Note

RAVENOL MARINE 1230 SAE 30 TBN12 is used as a lubrication oil in quickly running and so-called « medium speed » navy diesel engines, perhaps with turbo charging and when using distilled fuels.

Characteristics

- a very good oxidation resistance
- a stable viscosity index
- excellent dispersant and detergent characteristics
- a good neutralizing power to neutralize acid connections which occur when burning diesel fuels
- a good cleaning power
- a good corrosion protection
- a good foam prevention
- a low pourpoint
- a good water separation behaviour

Characteristics

<i>Title</i>	<i>Value</i>	<i>Audit</i>
API	CF	
Համապատասխանում է արտադրողի պահանջներին	DEF 91-22/2, MIL-L-2104 C	
Density at 20 °C	883 kg/m ³	EN ISO 12185
Գույն	Brown	տեսողական
Մածուցիկություն 100 °C-ում	11.7 mm ² /s	DIN 51562-1
Մածուցիկություն 40 °C-ում	105.2 mm ² /s	DIN 51562-1
Viscosity Index VI	99	DIN ISO 2909
Pourpoint	-21 °C	DIN ISO 3016
Flashpoint	274 °C	DIN EN ISO 2592
TBN	12.5 mgKOH/g	ASTM D2896
Sulphated Ash	1.67 %wt.	DIN 51575
Engine cycle	4T	

Out of production

<i>Product</i>	<i>Vendor</i>	<i>Barcode</i>
1 l	1163010-001-06-999	
10 l	1163010-010-01-999	