

RAVENOL SSG Spec Synt LKW Getriebeöl 75W-80

SAE: 75W-80

Synthetic



1 l

Vendor:
1221100-001



4 l

Vendor:
1221100-004



10 l

Vendor:
1221100-010
Vendor:
1221100-010-01-999
Barcode:
4014835733848



20 l

Vendor:
1221100-020
Vendor:
1221100-020-01-999
Barcode:
4014835733824



20 l, ecobox

Vendor:
1221100-B20



60 l

Vendor:
1221100-060



60 l, տպագիր տակառ

Vendor:
1221100-D60



208 l

Vendor:
1221100-208
Vendor:
1221100-208-01-999



208 Լ տպագիր տակառ

Vendor:
1221100-D28
Vendor:
1221100-D28-01-888
Barcode:
4014835733800



1 000 Լ

Vendor:
1221100-700

RAVENOL SSG Spec Synt LKW Getriebeoil 75W-80 is a synthetic low viscosity transmission oil specifically for highly stressed manual transmissions.

RAVENOL SSG Spec Synt LKW Getriebeoil 75W-80 is designed based on synthetic base oils and specially coordinated additive treatment. This exceeds the needs of today's application requirements.

RAVENOL SSG Spec Synt LKW Getriebeoil 75W-80 is outstanding for use under severe mechanical and thermal stress on transmission oils, even with extended oil change intervals.

Application Note

RAVENOL SSG Spec Synt LKW Getriebeoil 75W-80 is a heavy duty transmission oil to care for synchronised manual transmissions in commercial vehicles with intarder or retarder. Shift comfort is noticeably increased. Extreme oil change intervals according as specified by the manufacturer at up to 500,000 km reduce maintenance costs and increase cost-effectiveness.

Characteristics

- Excellent thermal stability
- High protection from rust, corrosion, foaming
- Low solidification point
- Excellent EP properties
- Good shifting behaviour in low temperatures
- Extended life
- Fuel savings

Characteristics

Title	Value	Audit
API	GL-4	
Հաստատված է արտադրողի կողմից	MAN 341 Type Z4, ZF TE-ML 01L, ZF TE-ML 02L, ZF TE-ML 16K	
Համապատասխանում է արտադրողի պահանջներին	DTFR 13D120 (MB 235.29), Eaton Extended drain, MAN 341 Type E3, MAN 341 Type VR, MAN 341 Type Z5, Voith Typ C, Volvo 97305, Volvo 97307, ZF TE-ML 01E, ZF TE-ML 02E, ZF TE-ML 16P	
Համապատասխանում է արտադրողի բնութագրերին	MIL-L-2105	
Suitable for	IVECO, Renault	
Density at 20 °C	855 kg/m ³	EN ISO 12185
Գույն	Red	տեսողական
Մածուցիկություն 100 °C-ում	9.29 mm ² /s	DIN 51562-1
Մածուցիկություն 40 °C-ում	51.97 mm ² /s	DIN 51562-1
Viscosity Index VI	163	DIN ISO 2909
Brookfield Viscosity at -40 °C	38.800 mPa*s	ASTM D2983
Pourpoint	-42 °C	DIN ISO 3016
Flashpoint	238 °C	DIN EN ISO 2592
Copper Strip Test at 121 °C	1b	ASTM D130

Analogs

Alpine

0101683, 0101684, 0101685

DAF

1659981, 09226BN, 1659989, 1659982, 1659982G, 09052IT, 09225RU, 09069RU, 09069EU, 1659988, 1659988G, 09069IT

FEBI

170126, 170127, 170134

Hyundai Motor

0450000440

MAN

09110700672

Pentosin

1027107

Porsche

00004330540, 00004330300

Volvo

85123561, 85113903, VPO120549, MVBVISHIFT75W80JUG, VPO120548, MVBVISHIFT75W80PAIL, 85136277, 85108170, 85123562, 85113904, 85136278, 85108171, 1161950

ZF

0671090386, S0671090384, S0671090386, 671090386, 0671090383, 671090383, S0671090383, 671090384, 0671090384, 0671090385, S0671090385, 671090385, S671090385

Out of production

<i>Product</i>	<i>Vendor</i>	<i>Barcode</i>
1 l	1221100-001-01-999 1221100-001-06-999	
4 l	1221100-004-01-999	
10 l	1221100-010-01-999	
20 l	1221100-020-01-000	4014835646421
20 l, ecobox	1221100-B20-01-888	
60 l	1221100-060-01-999	
208 l	1221100-208-01-888 1221100-208-01-999	
208 l	1221100-208-01-000 1221100-208-01-888	4014835646483