

RAVENOL TDG 75W-110

SAE: 75W-110

Full synthetic



1 L

Vendor:
1221109-001
 Vendor:
 1221109-001-01-999
 Barcode:
 4014835772113



4 L

Vendor:
1221109-004
 Vendor:
 1221109-004-01-999
 Barcode:
 4014835772199



10 L

Vendor:
1221109-010



20 L

Vendor:
1221109-020



60 L

Vendor:
1221109-060



60 L, տպագիր տակառ

Vendor:
1221109-D60



208 L

Vendor:
1221109-208



208 L, տպագիր տակառ

Vendor:
1221109-D28

RAVENOL TDG 75W-110 is full synthetic "Total Drive Line" low viscosity transmission oil.

RAVENOL TDG 75W-110 is designed based on synthetic base oils and specially coordinated additive treatment. This exceeds the needs of today's application requirements.

RAVENOL TDG 75W-110 is oil is developed for manual transmissions and hypoid differentials in passenger cars, delivery vans and heavy trucks.

Application Note

RAVENOL TDG 75W-110 is universal gear oil developed for manual transmissions and hypoid differentials in passenger cars, delivery vans and heavy trucks. This so called "Total Drive Line" oil is as universal product widely usable.

Characteristics

- Excellent thermal stability.
- High protection from rust, corrosion, foaming.
- Low solidification point.
- Excellent EP properties.
- Good shifting behaviour in low temperatures.
- Extended life.
- Fuel savings.

Characteristics

Title	Value	Audit
API	GL-4, GL-5, MT-1	
Հաստատված է արտադրողի կողմից	ZF TE-ML 05A, ZF TE-ML 12N, ZF TE-ML 16F, ZF TE-ML 21A	
Համապատասխանում է արտադրողի պահանջներին	MIL-L-2105 D, MIL-PRF-2105 E, Mack GO-J, SAE J 2360, Scania STO 2:0 A, ZF TE-ML 05B, ZF TE-ML 07A, ZF TE-ML 08, ZF TE-ML 19C, ZF TE-ML 21B	
Suitable for	DAF, IVECO	
Density at 20 °C	874 kg/m ³	EN ISO 12185
Գույն	Yellow	տեսողական
Մածուցիկություն 100 °C-ում	21.4 mm ² /s	DIN 51562-1
Մածուցիկություն 40 °C-ում	163.5 mm ² /s	DIN 51562-1
Viscosity Index VI	155	DIN ISO 2909
Brookfield Viscosity at -40 °C	98.700 mPa*s	ASTM D2983
Pourpoint	-45 °C	DIN ISO 3016
Flashpoint	216 °C	DIN EN ISO 2592
Copper Strip Test at 121 °C	1b	ASTM D130

Out of production

Product	Vendor	Barcode
10 l	1221109-010-01-999	
20 l	1221109-020-01-999	
60 l	1221109-060-01-999	
208 l	1221109-208-01-999	