

# RAVENOL MARINE PowerTrim & Steering Fluid

Mineral



**1 l**

Vendor:  
**1234100-001**  
Vendor:  
1234100-001-01-999  
Barcode:  
4014835735019



**4 l**

Vendor:  
**1234100-004**



**10 l**

Vendor:  
**1234100-010**



**20 l**

Vendor:  
**1234100-020**



**20 l, ecobox**

Vendor:  
**1234100-B20**



**60 l**

Vendor:  
**1234100-060**



**208 l**

Vendor:  
**1234100-208**



**1 000 l**

Vendor:  
**1234100-700**

**RAVENOL MARINE Power Trim & Steering Fluid** is a high quality hydraulic oil based on specially selected solvent refined base oils.

It is particularly characterized by a high and stable viscosity index and reliable corrosion protection. Effective additives provide an excellent wear protection even under extreme loads. The behaviour towards sealing materials is neutral.

## Application Note

**RAVENOL MARINE Power Trim & Steering Fluid** is an excellent product for lubrication of hydraulics in the marine area.

May not be used if in the hydraulic systems are silver and / or silver-plated construction and operating elements present.

## Characteristics

- A high and stable viscosity index
- Excellent protection against wear
- Widest possible protection against corrosion
- A very good air and water separation to prevent foaming
- A neutral attitude towards plastic and seals
- A very low pour point

## Characteristics

| Title                                   | Value                  | Audit           |
|---|------------------------|-----------------|
| Համապատասխանում է արտադրողի պահանջներին | Volvo PENTA            |                 |
| Suitable for                            | Mercruiser, Yanmar     |                 |
| Density at 20 °C                        | 845 kg/m <sup>3</sup>  | EN ISO 12185    |
| Գույն                                   | Blue                   | տեսողական       |
| Մածուցիկություն 100 °C-ում              | 6.3 mm <sup>2</sup> /s | DIN 51562-1     |
| Մածուցիկություն 40 °C-ում               | 32 mm <sup>2</sup> /s  | DIN 51562-1     |
| Viscosity Index VI                      | 152                    | DIN ISO 2909    |
| Pourpoint                               | -39 °C                 | DIN ISO 3016    |
| Flashpoint                              | 227 °C                 | DIN EN ISO 2592 |

## Analogs

### BRP

779481, 779752, 775612, 779759

### Yamalube

ACCPWRTRMF32, ACCPWRTRMF10

## Out of production

| Product | Vendor             | Barcode       |
|---------|--------------------|---------------|
| 1 l     | 1234100-001-01-100 | 4014835647114 |
|         | 1234100-001-06-999 | 2200000035684 |
| 4 l     | 1234100-004-01-999 |               |
| 10 l    | 1234100-010-01-999 |               |
| 20 l    | 1234100-020-01-999 |               |
| 60 l    | 1234100-060-01-999 |               |
| 208 l   | 1234100-208-01-999 |               |