

RAVENOL MOTOGEAR 75W-90 GL-4

SAE: 75W-90

Full synthetic



1 l

Vendor:
1250050-001
 Vendor:
 1250050-001-01-999
 Barcode:
 4014835735118



4 l

Vendor:
1250050-004
 Vendor:
 1250050-004-01-999
 Barcode:
 4014835735194



20 l

Vendor:
1250050-020



20 l, ecobox

Vendor:
1250050-B20

RAVENOL Motogear SAE 75W-90 GL-4 is a full synthetic gear oil with a special formulation for extremely stressed gearboxes and rear axles.

RAVENOL Motogear SAE 75W-90 GL-4 is designed on the basis of high-quality synthetic base oils with a special additivation and inhibition to ensure the proper operation of the transmission and the rear axle.

RAVENOL Motogear SAE 75W-90 GL-4 has good high temperature stability with a high load carrying capacity and reduces friction even under extreme operating conditions.

RAVENOL Motogear SAE 75W-90 GL-4 for comfortable operation even at low temperatures.

Application Note

RAVENOL Motogear SAE 75W-90 GL-4 is best for use in highly loaded gearboxes and rear axle - final drive, for which SAE 75W-90 API GL-4 oil is required.

Characteristics

- High load carrying capacity by a stable lubricating film even at high loads
- Reduction of friction and wear by special additives
- A very good corrosion protection and good tolerability to non-ferrous metal
- A high oxidative stability to prevent oil thickening and deposits
- Excellent cold flow properties
- a very good compatibility with elastomers to prevent leaks
- A very strong protection against rust, corrosion and foaming
- Excellent EP properties

Characteristics

Title	Value	Audit
API	GL-4	
Density at 20 °C	840 kg/m ³	EN ISO 12185
Գույն	Yellow	տեսողական
Մածուցիկություն 100 °C-ում	16.8 mm ² /s	DIN 51562-1
Մածուցիկություն 40 °C-ում	108.8 mm ² /s	DIN 51562-1
Viscosity Index VI	168	DIN ISO 2909
Brookfield Viscosity at -40 °C	47.000 mPa*s	ASTM D2983
Pourpoint	-54 °C	DIN ISO 3016
Flashpoint	230 °C	DIN EN ISO 2592
Copper Strip Test at 121 °C	1a	ASTM D130

Analogs

Honda

08268M99K0ZT1, 08268M99K0ZT3, 08294M99K8LT1, 08294M99K8LT3