

RAVENOL STOU 10W-30

SAE: 10W-30



5 l

Vendor:
1310100-005



20 l

Vendor:
1310100-020
Vendor:
1310100-020-01-999
Barcode:
4014835739529



20 l, ecobox

Vendor:
1310100-B20



60 l

Vendor:
1310100-060
Vendor:
1310100-060-01-999
Barcode:
4014835739567



208 l

Vendor:
1310100-208
Vendor:
1310100-208-01-999
Barcode:
4014835739581



1 000 l

Vendor:
1310100-700

RAVENOL STOU SAE 10W-30 is a multifunctional lubricating oil for agricultural machinery, excavators and construction machinery and is formulated with top-grade solvent refined base oils and additives.

RAVENOL STOU SAE 10W-30 meets the recommendations of all well known tractor manufacturers and is equal to use in engines, transmissions and hydraulic systems of modern tractors. Ensures trouble-free operation of all units in all seasons. Suitable for wet brakes and shaft coupling (PTO clutches).

Application Note

RAVENOL STOU SAE 10W-30 has a wide range of applications in engines, transmissions and hydraulic systems of modern tractors.

RAVENOL STOU SAE 10W-30 is suitable as an engine oil for gasoline engines and intake and turbo charged diesel engines, also as gear oil (including wet brakes) and as hydraulic oil.

Characteristics

- A powerful dispersion and detergency
- Protection against wear, corrosion and foam
- High resistance to oxidation
- Excellent extreme pressure properties
- A high and stable viscosity index

Characteristics

Title	Value	Audit
API	CG-4, GL-4, SF	
ACEA	E3	
Համապատասխանում է արտադրողի պահանջներին	Allison C-4, Caterpillar TO-2, DTFR 15B110 (MB 228.3), Ford ESN-M2C 159-B, ISO VG 68 HVLP, John Deere J27, Kompressorenöl: Holman Compair Kompressor, MAN 270, MB 227.1, MB 228.1, MB 228.3, MIL-L-2104 D, Massey Ferguson CMS M1139, Massey Ferguson CMS M1144, Massey Ferguson CMS M1145, New Holland ESN-M2C 159-B, ZF TE-ML 06A, ZF TE-ML 06B, ZF TE-ML 06D, ZF TE-ML 07B	
Suitable for	Atlas Copco Kompressor	
Density at 20 °C	867 kg/m ³	EN ISO 12185
Գույն	tan	տեսողական
Մածուցիկություն 100 °C-ում	11.7 mm ² /s	DIN 51562-1
Մածուցիկություն 40 °C-ում	74.7 mm ² /s	DIN 51562-1
Viscosity Index VI	151	DIN ISO 2909
Pourpoint	-36 °C	DIN ISO 3016
Flashpoint	226 °C	DIN EN ISO 2592
TBN	12.4 mgKOH/g	ASTM D2896
Sulphated Ash	1.58 %wt.	DIN 51575

Analogs

Isuzu

985531930A, 1884057500, 1884057520, 1884057720

Out of production

Product	Vendor	Barcode
208 l	1310100-208-01-999	
208 l	1310100-208-01-000	4014835636484 2200000046215