

RAVENOL STOU 15W-30

SAE: 15W-30

Mineral



20 լ

Vendor:
1310112-020



20 լ, ecobox

Vendor:
1310112-B20



60 լ

Vendor:
1310112-060
Vendor:
1310112-060-01-999
Barcode:
4014835739963



60 լ, տպագիր տակառ

Vendor:
1310112-D60



208 լ

Vendor:
1310112-208



1 000 լ

Vendor:
1310112-700

RAVENOL STOU SAE 15W-30 is a multi-purpose super universal tractor oil for agricultural machinery, excavators and construction equipment made from specially selected solvent-refined base oils. It is formulated to meet the requirements of all major tractor manufacturers as listed below, and can be used in engines, transmissions and hydraulic systems of most equipment in all seasons which require this grade of oil.

Application Note

RAVENOL STOU SAE 15W-30 has a wide range of applications in engines, transmissions and hydraulic systems of many tractors and is suitable for use as motor oil for both petrol and diesel engines, transmission oil (including wet brakes and PTO transmissions) and as a hydraulic oil where this specification of product is required. Can also be used as compressor oil.

Characteristics

- Excellent viscosity-temperature behaviour
- Exceptional cold starting abilities
- Excellent detergent and dispersant properties
- High resistance to ageing

Characteristics

Title	Value	Audit
API	CE, GL-4, SF	
ACEA	E1, E2	
Համապատասխանում է արտադրողի պահանջներին	Allison C-4, Case IH International J I, Case IH MS 1118, Case IH MS 1206, Case IH MS 1209, Caterpillar TO-2, Fiat AF 87, Ford NH 024C, Ford NH 324B, Ford NH 540B, Ford Pumpentest, ISO VG 68 HLP, International Harvester B6, John Deere J20 C, John Deere J20 D, John Deere J27A, Kompressorenöl: Holman Compair Kompressor, MIL-L-2105, Massey Ferguson CMS M1127, Massey Ferguson CMS M1139, Massey Ferguson CMS M1144, Parker Denison HF-2, Vickers Pumpentest, ZF TE-ML 06B, ZF TE-ML 07B	
Suitable for	Atlas Copco Kompressor	
Density at 20 °C	861 kg/m ³	EN ISO 12185
Գույն	tan	տեսողական
Մածուցիկություն 100 °C-ում	11.8 mm ² /s	DIN 51562-1
Մածուցիկություն 40 °C-ում	71.7 mm ² /s	DIN 51562-1
Viscosity Index VI	159	DIN ISO 2909
Pourpoint	-39 °C	DIN ISO 3016
Flashpoint	222 °C	DIN EN ISO 2592
TBN	11.7 mgKOH/g	ASTM D2896
Sulphated Ash	1.5 %wt.	DIN 51575

Out of production

Product	Vendor	Barcode
20 l	1310112-020-01-999	
60 l	1310112-060-01-000	4014835636064
208 l	1310112-208-01-999	