

# RAVENOL STOU 15W-40

**SAE: 15W-40****Mineral****5 l**

Vendor:  
**1310113-005**  
Vendor:  
1310113-005-01-999

**10 l**

Vendor:  
**1310113-010**  
Vendor:  
1310113-010-01-999  
Barcode:  
W24001055

**20 l**

Vendor:  
**1310113-020**  
Vendor:  
1310113-020-01-999  
Barcode:  
4014835740020

**20 l, ecobox**

Vendor:  
**1310113-B20**

**60 l**

Vendor:  
**1310113-060**  
Vendor:  
1310113-060-01-999

**208 l**

Vendor:  
**1310113-208**  
Vendor:  
1310113-208-01-999

**1 000 l**

Vendor:  
**1310113-700**

**RAVENOL STOU SAE 15W-40** is up-to-date multifunctional STOU (Super Tractor Oil Universal) lubricating oil for agricultural machinery, excavators and construction machinery and is formulated with top-grade solvent refined base oils. It is a special fluid which meets the recommendations of agricultural machinery manufacturers.

**RAVENOL STOU SAE 15W-40** is equal to use in engines, transmissions and hydraulic systems of modern tractors. Top-grade solvent refined base oils and special synthetic based additives ensure trouble-free operation of all units in all seasons.

## Application Note

**RAVENOL STOU SAE 15W-40** has a wide range of applications in engines, transmissions and hydraulic systems of modern tractors.

**RAVENOL STOU SAE 15W-40** is suitable as an engine oil for gasoline engines and intake and turbo charged diesel engines, also as gear oil (including wet brakes) and as hydraulic oil.

## Characteristics

- A powerful dispersion and detergency
- A high activity against wear, corrosion and foam
- A very strong resistance to oxidation
- Excellent extreme pressure properties
- A high and stable viscosity index

## Characteristics

Title	Value	Audit
API	CE, CF-4, GL-4, SF	
ACEA	E1	
Համապատասխանում է արտադրողի պահանջներին	Allison C-4, Caterpillar TO-2, Ford ESN-M2C 134-D, Ford ESN-M2C 159-C, Ford ESN-M2C 86-A, John Deere J27, MB 227.1, Massey Ferguson CMS M1143, Massey Ferguson CMS M1144, New Holland 410B, New Holland 420A, ZF TE-ML 06B, ZF TE-ML 07B	
Համապատասխանում է արտադրողի բնութագրերին	CCMC D4, CCMC G2	
Density at 20 °C	865 kg/m <sup>3</sup>	EN ISO 12185
Գույն	Brown	տեսողական
Մածուցիկություն 100 °C-ում	13.3 mm <sup>2</sup> /s	DIN 51562-1
Մածուցիկություն 40 °C-ում	94.2 mm <sup>2</sup> /s	DIN 51562-1
Viscosity Index VI	141	DIN ISO 2909
Pourpoint	-36 °C	DIN ISO 3016
Flashpoint	228 °C	DIN EN ISO 2592
TBN	12.8 mgKOH/g	ASTM D2896

## Analogs

### Volvo

1161930, 1161908