

RAVENOL STOU 20W-40

SAE: 20W-40



20 l

Vendor:
1310114-020
Vendor:
1310114-020-01-999
Barcode:
4014835740129



20 l, ecobox

Vendor:
1310114-B20



60 l

Vendor:
1310114-060



208 l

Vendor:
1310114-208
Vendor:
1310114-208-01-999
Barcode:
4014835740181



1 000 l

Vendor:
1310114-700

RAVENOL STOU SAE 20W-40 is up-to-date multifunctional STOU (Super Tractor Oil Universal) lubricating oil for agricultural- and earthmoving equipment, formulated with top-grade solvent refined base oils. It is a special fluid which meets the recommendations of agricultural machinery manufacturers.

RAVENOL STOU SAE 20W-40 is equal to use in engines, transmissions and hydraulic systems of modern tractors. Top-grade solvent refined base oils and special synthetic based additives ensure trouble-free operation of all units in all seasons.

Application Note

RAVENOL STOU SAE 20W-40 has a wide range of applications in engines, transmissions and hydraulic systems of modern tractors.

RAVENOL STOU SAE 20W-40 is suitable as an engine oil for gasoline engines and intake and turbo charged diesel engines, also as gear oil (including wet brakes) and as hydraulic oil.

Characteristics

- A powerful dispersion and detergency
- A high activity against wear, corrosion and foam
- A very strong resistance to oxidation
- Excellent extreme pressure properties
- A high and stable viscosity index

Characteristics

Title	Value	Audit
API	CG-4, GL-4, SF	
ACEA	E3	
Համապատասխանում է արտադրողի պահանջներին	Allison C-4, Caterpillar TO-2, Ford ESN-M2C 134-D, Ford ESN-M2C 159-C, MB 227.1, MIL-L-2104 D, Massey Ferguson CMS M1143, Massey Ferguson CMS M1144, Massey Ferguson CMS M1145, ZF TE-ML 06B, ZF TE-ML 07B	
Density at 20 °C	883 kg/m ³	EN ISO 12185
Գույն	tan	տեսողական
Մածուցիկություն 100 °C-ում	13.1 mm ² /s	DIN 51562-1
Մածուցիկություն 40 °C-ում	111.8 mm ² /s	DIN 51562-1
Viscosity Index VI	112	DIN ISO 2909
Pourpoint	-30 °C	DIN ISO 3016
Flashpoint	246 °C	DIN EN ISO 2592
TBN	13 mgKOH/g	ASTM D2896
Sulphated Ash	1.5 %wt.	DIN 51575
CCS Viscosity at -15 °C	6860 mPa*s	ASTM D5293

Analogs

Yamalube
ACCTRANSPLUS

Out of production

Product	Vendor	Barcode
60 l	1310114-060-01-999	