

# RAVENOL Catoel TO-4 40

**SAE: 40W**

**Mineral**



**20 l**

Vendor:  
**1310614-020**  
 Vendor:  
 1310614-020-01-999



**20 l, ecobox**

Vendor:  
**1310614-B20**



**208 l**

Vendor:  
**1310614-208**



**1 000 l**

Vendor:  
**1310614-700**

**RAVENOL CATOEL TO-4 SAE 40** is a special transmission oil developed specifically to meet the stringent requirements of the Caterpillar TO-4 specification. It ensures maximum wear protection in different gears, like side drives and differentials optimized friction coefficient in the power-shift transmissions, wet brakes and clutches and provides maximum service life of the units.

## Application Note

**RAVENOL CATOEL TO-4 SAE 40** is formulated to meet the stringent Caterpillar TO-4 specification, and is suitable for use in transmissions, final drives, hydraulic systems, wet brakes and clutches that require this specification of lubricant.

## Characteristics

- Highest wear protection
- High oxidation stability
- Excellent viscosity-temperature behavior

- Optimization of friction coefficient behavior
- Guarantees maximum life of the units

## Characteristics

Title	Value	Audit
API	CF, MT-1	
Համապատասխանում է արտադրողի պահանջներին	Allison C-4, Caterpillar TO-4, Komatsu KES 07.868.1 (2002), ZF TE-ML 03C, ZF TE-ML 07F	
Suitable for	Eaton Fuller	
Density at 20 °C	889 kg/m <sup>3</sup>	EN ISO 12185
Գույն	tan	տեսողական
Մածուցիկություն 100 °C-ում	13.6 mm <sup>2</sup> /s	DIN 51562-1
Մածուցիկություն 40 °C-ում	134 mm <sup>2</sup> /s	DIN 51562-1
Viscosity Index VI	96	DIN ISO 2909
Pourpoint	-21 °C	DIN ISO 3016
Flashpoint	270 °C	DIN EN ISO 2592

## Out of production

Product	Vendor	Barcode
208 լ	1310614-208-01-999	