

RAVENOL Hydraulikoel TS 15 (HLP)

SAE: 15**Mineral****1 l**

Vendor:
1323102-001
Vendor:
1323102-001-01-999

**5 l**

Vendor:
1323102-005
Vendor:
1323102-005-01-999

**20 l**

Vendor:
1323102-020
Vendor:
1323102-020-01-999

**20 l, ecobox**

Vendor:
1323102-B20

**60 l**

Vendor:
1323102-060
Vendor:
1323102-060-01-999

**208 l**

Vendor:
1323102-208
Vendor:
1323102-208-01-999

**1 000 l**

Vendor:
1323102-700

RAVENOL Hydraulikoel TS 15 (HLP) is optimal alloyed mineral hydraulic oil with a high performance level and a wide application area of the whole industry.

RAVENOL Hydraulikoel TS 15 (HLP) with efficient additives offers an excellent corrosion protection even under extreme loads. The behaviour of sealing materials is neutral.

RAVENOL Hydraulikoel TS 15 (HLP) is characterised by good viscosity temperature behaviour, a high aging resistant and a solid corrosion protection.

Application Note

RAVENOL Hydraulikoel TS 15 (HLP) is for universal use in all hydraulic systems.

RAVENOL Hydraulikoel TS 15 (HLP) is recommended in high performance hydraulic systems with high pressure pumps of all types, in sensitive control systems.

RAVENOL Hydraulikoel TS 15 (HLP) is used for hydraulic systems in agriculture, to supply small gearboxes and for use in circulating systems.

Characteristics

- a high performance level
- a very good viscosity temperature behaviour
- a high aging resistant
- an excellent corrosion protection
- a solid corrosion protection
- neutrality of sealing materials

Characteristics

Title	Value	Audit
ASTM	D6158	
Համապատասխանում է արտադրողի պահանջներին	AFNOR NFE 48-603 HM, Bosch Rexroth RE 90220, Cetop RP 91H HM, Cincinnati Milacron P-68, Cincinnati Milacron P-69, Cincinnati Milacron P-70, Danieli Hydraulics, FZG Test A 8,3/90, GB 111118.1 L-HL, ISO 11158 HM, MIL-H-24459, Parker Denison HF-0, Parker Denison HF-2, SAE MS 1004 HM, Sauer-Danfoss 520L0463, Swedish Standard 155434, VDMA 24318	
Համապատասխանում է արտադրողի բնութագրերին	DIN 51524-2, ISO 6743-4 HM	
Suitable for	Metso	
Density at 20 °C	837 kg/m ³	EN ISO 12185
Գույն	light yellow	տեսողական
Մածուցիկություն 100 °C-ում	3.5 mm ² /s	DIN 51562-1
Մածուցիկություն 40 °C-ում	15 mm ² /s	DIN 51562-1
Viscosity Index VI	113	DIN ISO 2909
Pourpoint	-51 °C	DIN ISO 3016
Flashpoint	186 °C	DIN EN ISO 2592

Analogs

Volvo

3809447, 21732287, 22618337

Out of production

Product	Vendor	Barcode
1 l	1323102-001-06-999	