

RAVENOL Hydraulikoel TS 22 (HLP)

SAE: 22

Mineral



1 l

Vendor:
1323103-001



5 l

Vendor:
1323103-005



10 l

Vendor:
1323103-010



20 l

Vendor:
1323103-020
Vendor:
1323103-020-01-999
Barcode:
4014835759220



20 l, ecobox

Vendor:
1323103-B20



60 l

Vendor:
1323103-060



208 l

Vendor:
1323103-208
Vendor:
1323103-208-01-999
Barcode:
4014835759282



1 000 l

Vendor:
1323103-700

RAVENOL Hydraulikoel TS 22 (HLP) is optimal alloyed mineral hydraulic oil with a high performance level and a wide application area of the whole industry.

RAVENOL Hydraulikoel TS 22 (HLP) with efficient additives offers an excellent corrosion protection even under extreme loads. The behaviour of sealing materials is neutral.

RAVENOL Hydraulikoel TS 22 (HLP) is characterised by good viscosity temperature behaviour, a high aging resistant and a solid corrosion protection.

Application Note

RAVENOL Hydraulikoel TS 22 (HLP) is for universal use in all hydraulic systems.

RAVENOL Hydraulikoel TS 22 (HLP) is recommended in high performance hydraulic systems with high pressure pumps of all types, in sensitive control systems.

RAVENOL Hydraulikoel TS 22 (HLP) is used for hydraulic systems in agriculture, to supply small gearboxes and for use in circulating systems.

Characteristics

- a high performance level
- a very good viscosity temperature behaviour
- a high aging resistant
- an excellent corrosion protection
- a solid corrosion protection
- neutrality of sealing materials

Characteristics

Title	Value	Audit
ASTM	D6158	
Համապատասխանում է արտադրողի պահանջներին	AFNOR NFE 48-603 HM, Bosch Rexroth RE 90220, Cetop RP 91H HM, Cincinnati Milacron P-68, Cincinnati Milacron P-69, Cincinnati Milacron P-70, Danieli Hydraulics, FZG Test A 8,3/90, GB 111118.1 L-HM, GM LH-02-1-04, GM LS-2, ISO 11158 HM, Parker Denison HF-0, Parker Denison HF-1, Parker Denison HF-2, SAE MS 1004 HM, SEB 181.222, Sauer-Danfoss 520L0463, Swedish Standard 155434, VDMA 24318, Vickers Pumpentest	
Համապատասխանում է արտադրողի բնութագրերին	DIN 51524-2, ISO 6743-4 HM	
Suitable for	Metso	
Density at 20 °C	843 kg/m ³	EN ISO 12185
Գույն	Yellow	տեսողական
Մածուցիկություն 100 °C-ում	4.5 mm ² /s	DIN 51562-1
Մածուցիկություն 40 °C-ում	22.6 mm ² /s	DIN 51562-1
Viscosity Index VI	114	DIN ISO 2909
Pourpoint	-39 °C	DIN ISO 3016
Flashpoint	214 °C	DIN EN ISO 2592
Ծերացման կայունություն, TOST	2000 st	DIN 51587

Out of production

Product	Vendor	Barcode
1 l	1323103-001-01-999 1323103-001-06-999	
5 l	1323103-005-01-999	
10 l	1323103-010-01-999	
20 l	1323103-020-01-000	4014835641525 2200000039859 2200000040176
60 l	1323103-060-01-999	
208 l	1323103-208-01-999 1323103-208-01-000	2200000042637 4014835641587
208 l	1323103-208-01-000 1323103-208-01-909	4014835641587 4014835799882 2200000042637