

# RAVENOL Hydraulikoel TS AF 68

SAE: 68

Mineral

20 L

Vendor:

**1323126-020**

Vendor:

1323126-020-01-999

60 L

Vendor:

**1323126-060**

Vendor:

1323126-060-01-999

208 L

Vendor:

**1323126-208**

Vendor:

1323126-208-01-999

## RAVENOL Hydraulikoel TS AF 68

is a zinc and ash-free compounded oil based phosphorous and sulfur intended especially for use in the metal industry. Excellent results were achieved in the Timken test. Through the addition of selected ingredients,

## RAVENOL Hydraulikoel TS AF 68

has excellent wear protection, good oxidation stability and has a long service life even under extreme conditions. Compatibility with sealants is neutral. Furthermore, the additives provide corrosion protection and prevent foaming.

## RAVENOL Hydraulikoel TS AF 68

exceeds the requirements of DIN 51 524 part 2 for HLP hydraulic oils.

## Application Note

## **RAVENOL Hydrauliköl TS AF 6**

is for use as a hydraulic fluid in the metal industry, if zinc and ash-free hydraulic oil and the specification DIN 51 524, Part 2 is required.

## Characteristics

<b>Title</b>	<b>Value</b>	<b>Audit</b>
Համապատասխանում է արտադրողի պահանջներին	MAN N 698, SEB 181.222, SEB 181.226, Timken- Test DIN E 51434	
Համապատասխանում է արտադրողի բնութագրերին	DIN 51524-2	
Density at 20 °C	866.1 kg/m³	EN ISO 12185
Գույն	tan	սետողական
Մածուցիկություն 100 °C-ում	9.1 mm²/s	DIN 51562-1
Մածուցիկություն 40 °C-ում	68.1 mm²/s	DIN 51562-1
Viscosity Index VI	108	DIN ISO 2909
Pourpoint	-24 °C	DIN ISO 3016
Flashpoint	249 °C	DIN EN ISO 2592