

# RAVENOL Kompressoren-Oel VDL 100

SAE: 100

Mineral



**1 l**

Vendor:  
**1330100-001**  
 Vendor:  
 1330100-001-01-999  
 Barcode:  
 4014835736115



**5 l**

Vendor:  
**1330100-005**  
 Vendor:  
 1330100-005-01-999  
 Barcode:  
 4014835736153



**10 l**

Vendor:  
**1330100-010**  
 Vendor:  
 1330100-010-01-999  
 Barcode:  
 4014835736146



**20 l**

Vendor:  
**1330100-020**  
 Vendor:  
 1330100-020-01-999  
 Barcode:  
 4014835736122



**20 l, ecobox**

Vendor:  
**1330100-B20**



**60 l**

Vendor:  
**1330100-060**



**208 l**

Vendor:  
**1330100-208**  
 Vendor:  
 1330100-208-01-999  
 Barcode:  
 4014835736184



**1 000 l**

Vendor:  
**1330100-700**

**RAVENOL Kompressorenöl VDL 100** meets the high requirements of DIN 51 506. Specially designed with high quality, age-resistant base oils.

**RAVENOL Kompressorenöl VDL 100** has a good adhesion, is water repellent and wear reducing. As many compressors operate at high temperatures, the oil should have good aging resistance at very low residue formation.

**RAVENOL Kompressorenöl VDL 100** provides a secure lubrication not only in the upper temperature range, also in the cold state of the compressor to achieve a reduction of wear. By selected and coordinated additive composition the tendency to coking and the formation of flammable residues is minimized.

## Application Note

**RAVENOL Kompressorenöl VDL 100** can be used in stationary and mobile compressors with discharge temperatures up to 220°C.

**RAVENOL Kompressorenöl VDL 100** can also be used for lubrication of engines and diesel engines where the manufacturer does not stipulate any HD motor oil.

## Characteristics

- Excellent aging resistance
- Best wear protection
- Excellent viscosity-temperature behavior
- Very good cold starting properties
- Low coking tendency

## Characteristics

Title	Value	Audit
Համապատասխանում է արտադրողի բնութագրերին	DIN 51 506 VCL	
Suitable for	ABAC, ALUP, Atlas Copco Kompressor, CompAir, FIAC, FINI, KAESER	
Density at 20 °C	881 kg/m <sup>3</sup>	EN ISO 12185
Գույն	tan	տեսողական
Մածուցիկություն 100 °C-ում	11.2 mm <sup>2</sup> /s	DIN 51562-1
Մածուցիկություն 40 °C-ում	100.2 mm <sup>2</sup> /s	DIN 51562-1
Viscosity Index VI	97	DIN ISO 2909
Pourpoint	-22 °C	DIN ISO 3016
Flashpoint	235 °C	DIN EN ISO 2592

## Analogs

### Alpine

0100984, 0100980, 0100981, 0100983, 0100985

## Out of production

Product	Vendor	Barcode
1 l	1330100-001-01-100	4014835650817
	1330100-001-06-999	2200000032393
5 l	1330100-005-01-100	4014835650855
		2200000019592
20 l	1330100-020-01-100	2200000022905
		4014835650824
60 l	1330100-060-01-999	2200000026606
		2200000027481