

RAVENOL Amber Getriebefließfett



25 kg

Vendor:
1340106-025



180 kg

Vendor:
1340106-180
Vendor:
1340106-180-03-000
Barcode:
4014835201071

RAVENOL Amber Getriebefließfett is a high-quality lithium saponified multi-purpose grease based on highly viscous paraffinic base oils with EP additives, which do not contain heavy metals or chlorine.

Application Note

RAVENOL Amber Getriebefließfett is particularly suitable for lubrication under the following unfavourable conditions: High surface pressure, irregular impact loads, wet conditions, soiling.

RAVENOL Amber Getriebefließfett is used in central lubrication systems of truck trailers.

RAVENOL Amber Getriebefließfett is also used for the lubrication of heavy duty roller and ball bearings in the industrial sector, mainly for low speeds.

Characteristics

- Excellent EP effect and wear protection
- Outstanding oxidation and corrosion protection even in the presence of moisture
- Very good mechanical stability
- Excellent resistance to water
- Long service life and therefore, longer lubrication intervals possible
- Excellent resistance to ageing
- Good pumpability, even at low temperatures

Characteristics

Title	Value	Audit
Համապատասխանում է արտադրողի բնութագրերին	DIN 51502 GP0K-30, ISO 6743-9: ISO-L-XCCFB0	
Գույն	Brown	տեսողական
Thickener	lithium soap	DIN 51757
NLGI-Class	0	DIN 51818
Product Classification	GP0K-30	DIN 51502
Working Temperature	-30 / +120 °C	DIN 51825
Short term temperature up to	120 °C	DIN 51757
Worked Penetration at 60 Strokes	355-385 mm/10/25°C	ISO 2137
Corrosion (SKF Emcors dist. Water)	1 Korr. Grad	DIN 51802
Dropping Point	185 °C	DIN ISO 2176
Copper Corrosion (24h/120 °C)	1	DIN 51811
Water Resistance (3h/90 °C)	1-90 °C	DIN 51807-1
VKA Pressure Carrying Capacity	2000 N	DIN 51350-4
Kinematic Viscosity (Base Oil) at 40 °C	65 mm ² /s	DIN 51562-1

Out of production

Product	Vendor	Barcode
25 կգ	1340106-025-03-000	