

RAVENOL Hot Red Grease HRG 1



1 կգ

Vendor:
1340120-001
 Vendor:
 1340120-001-03-999
 Barcode:
 4014835756410



5 կգ

Vendor:
1340120-005
 Vendor:
 1340120-005-03-999
 Barcode:
 4014835756458



10 կգ

Vendor:
1340120-010



15 կգ

Vendor:
1340120-015
 Vendor:
 1340120-015-03-999
 Barcode:
 4014835756465



25 կգ

Vendor:
1340120-025
 Vendor:
 1340120-025-03-999
 Barcode:
 4014835756472



180 կգ

Vendor:
1340120-180
 Vendor:
 1340120-180-03-999
 Barcode:
 4014835756489

RAVENOL Hot Red Grease HRG 1

is a red lithium complex soap lubricating grease based on high quality base oils. Excellent work resistance, rust and corrosion protection. Application for the lubrication of roller and friction bearings under extreme pressure at high bearing temperatures. Particularly recommended for the lubrication of wheel bearings on commercial vehicles and for high-speed passenger car wheel bearings.

Application Note

RAVENOL Hot Red Grease HRG

is used as an universal grease in the industrial sector and in the motor vehicle sector.

RAVENOL Hot Red Grease HRG

is particularly recommended as a grease for friction and roller bearings on motor vehicles, equipment, machinery, conveyors, construction vehicles, etc.

Characteristics

Title	Value	Audit
Համապատասխանում է արտադրողի բնութագրերին	DIN 51502 KP1P-35, ISO 6743-9: ISO-L-XCEEB1	
Գույն	reddish brown	տեսողական
Thickener	lithium soap	DIN 51757
NLGI-Class	1	DIN 51818
Product Classification	KP1P-35	DIN 51502
Working Temperature	-35 / +160 °C	DIN 51825
Short term temperature up to	200 °C	DIN 51757
Worked Penetration at 60 Strokes	310-340 mm/10/25°C	ISO 2137
Corrosion (SKF Emscor dist. Water)	0 Korr. Grad	DIN 51802
Dropping Point	260 °C	DIN ISO 2176
Copper Corrosion (24h/120 °C)	1	DIN 51811
Water Resistance (3h/90 °C)	1-90 °C	DIN 51807-1
VKA Pressure Carrying Capacity	2200 - 2400 N	DIN 51350-4
Kinematic Viscosity (Base Oil) at 40 °C	140 mm ² /s	DIN 51562-1

Analogs

Caterpillar

4525996