

RAVENOL Hot Red Grease HRG 3



1 կգ

Vendor:
1340122-001
 Vendor:
 1340122-001-03-999
 Barcode:
 4014835756618



5 կգ

Vendor:
1340122-005
 Vendor:
 1340122-005-03-999
 Barcode:
 4014835756656



10 կգ

Vendor:
1340122-010
 Vendor:
 1340122-010-03-999
 Barcode:
 4014835756632



15 կգ

Vendor:
1340122-015
 Vendor:
 1340122-015-03-999
 Barcode:
 4014835756663



25 կգ

Vendor:
1340122-025
 Vendor:
 1340122-025-03-999
 Barcode:
 4014835756670



100 գրամ

Vendor:
1340122-100
 Vendor:
 1340122-100-04-999
 Barcode:
 4014835844698



180 կգ

Vendor:
1340122-180
 Vendor:
 1340122-180-03-999
 Barcode:
 4014835756687



400 գրամ

Vendor:
1340122-400
 Vendor:
 1340122-400-04-999
 Barcode:
 4014835756649

RAVENOL Hot Red Grease HRG 3 is a red lithium complex soap lubricating grease on the basis of high quality base oils. Excellent work resistance, rust and corrosion protection. Application for the lubrication of

roller and friction bearings under extreme pressure at high bearing temperatures. Particularly recommended for the lubrication of wheel bearings on commercial vehicles and for high-speed passenger car wheel bearings.

Application Note

RAVENOL Hot Red Grease HRG 3 is used for the lubrication of roller and friction bearings under extreme pressure at high bearing temperatures.

RAVENOL Hot Red Grease HRG 3 is particularly recommended for the lubrication of commercial vehicles and for high-speed passenger car wheel bearings.

Characteristics

Title	Value	Audit
Համապատասխանում է արտադրողի բնութագրերին	DIN 51502 KP3P-25, ISO 6743-9: ISO-L-XBEEB3	
Գույն	Red	տեսողական
Thickener	lithium soap	DIN 51757
NLGI-Class	3	DIN 51818
Product Classification	KP3P-25	DIN 51502
Working Temperature	-25 / +160 °C	DIN 51825
Short term temperature up to	200 °C	DIN 51757
Worked Penetration at 60 Strokes	220-250 mm/10/25°C	ISO 2137
Corrosion (SKF Emscor dist. Water)	0 Korr. Grad	DIN 51802
Dropping Point	260 °C	DIN ISO 2176
Copper Corrosion (24h/120 °C)	1	DIN 51811
Water Resistance (3h/90 °C)	1-90 °C	DIN 51807-1
VKA Pressure Carrying Capacity	2600 - 2800 N	DIN 51350-4
Kinematic Viscosity (Base Oil) at 40 °C	150 mm ² /s	DIN 51562-1

Analogs

Land Rover

LR078521