

RAVENOL Bettbahnoel 68

SAE: 68

Mineral



5 l

Vendor:
1350376-005



20 l

Vendor:
1350376-020
Vendor:
1350376-020-01-999
Barcode:
4014835763425



60 l

Vendor:
1350376-060



208 l

Vendor:
1350376-208
Vendor:
1350376-208-01-999

RAVENOL Bettbahnoel 68 is mineral slide way oil CGLP.

RAVENOL Bettbahnoel 68 is characterized by good lubricating and sliding properties as well as high tackiness.

RAVENOL Bettbahnoel 68 is formulated with mineral base oils and contains additives and corrosion inhibitors to prevent rust formation and stains on slide ways and track surfaces.

RAVENOL Bettbahnoel 68 is compatible with most of drilling-, cutting or grinding emulsions. The lubricant film of the slide way oil is not washed off.

Application Note

RAVENOL Bettbahnoel 68 can be used for all types of lubrication systems such as pressure, circulating or central lubrication. If necessary, it can be applied manually. It can also be used for lubricating bearings and gear boxes.

Characteristics

- Very good stick-slip characteristics
- High tackiness
- Good corrosion protection, no rust and stain formation
- Resistance to aqueous metalworking fluids
- Good demulsification

Characteristics

<i>Title</i>	<i>Value</i>	<i>Audit</i>
Համապատասխանում է արտադրողի բնութագրերին	DIN 51502 CGLP, DIN 51517-3, DIN 51524-2	
Density at 20 °C	869 kg/m ³	EN ISO 12185
Գույն	Yellow	տեսողական
Մածուցիկություն 100 °C-ում	8.8 mm ² /s	DIN 51562-1
Մածուցիկություն 40 °C-ում	66.6 mm ² /s	DIN 51562-1
Viscosity Index VI	104	DIN ISO 2909
Pourpoint	-27 °C	DIN ISO 3016
Flashpoint	256 °C	DIN EN ISO 2592

Out of production

<i>Product</i>	<i>Vendor</i>	<i>Barcode</i>
60 l	1350376-060-01-999	