

RAVENOL OTC HOT CLIMATE-15C Protect C12+

**1,5 l**

Vendor:
1410113-150
Vendor:
1410113-150-01-999

**5 l**

Vendor:
1410113-005
Vendor:
1410113-005-01-999

**10 l**

Vendor:
1410113-010

**20 l**

Vendor:
1410113-020
Vendor:
1410113-020-01-999

**60 l**

Vendor:
1410113-060
Vendor:
1410113-060-01-999

**208 l**

Vendor:
1410113-208
Vendor:
1410113-208-01-999

**1 000 l**

Vendor:
1410113-700

RAVENOL OTC Org. Techn. Coolant HOT CLIMATE -15°C is a ready-to-use, prediluted with water, eco-friendly 1.2- Ethanediol (monoethylene glycol) based silicate, borate, nitrite and phosphate-free coolant for

cooling circuits in combustion engines which provides maintenance-free corrosion and frost protection. This product is formulated based on a proven inhibitor development with the organic additive technology OAT as an extended life coolant.

The quality of an antifreeze is no longer just determined by the antifreeze effect (which automatically exists in an ethylene-glycol based product), but by the rust protection. That is why automakers subject antifreeze to lengthy corrosion and cavitation tests.

RAVENOL OTC Org. Techn. Coolant HOT CLIMATE -15°C protects the cooling system from rust, frost, and in summer, from overheating.

Application Note

RAVENOL OTC Org. Techn. Coolant HOT CLIMATE -15°C is a prediluted coolant with frost and rust protection for year-round use in automotive engines.

Even in summer coolant must contain enough antifreeze to ensure good corrosion and overheating protection.

Instructions: Add **RAVENOL OTC Org. Techn. Coolant HOT CLIMATE -15°C** to radiator to fill line.

Characteristics

- Excellent for light metal engines
- Good reserve alkalinity
- Premium corrosion additives for optimal rust protection for all metals and metal alloys used in coolsystems, including aluminium
- Prevents sediments and foaming in the cooling system
- Compatible with elastomers used in automotive radiators
- Can be mixed with other coolant types

Characteristics

Title	Value	Audit
Համապատասխանում է արտադրողի պահանջներին	DAF 74002, DTFR 29C110 (MB 325.3), Deutz DQC CB-14, Ford WSS-M97 B44-D, GM 6277 M, GM B0401065, MAN 324 Type SNF, MB 325.3, SAE J 1034, VW G 012 A8F, VW TL 774-D, VW TL 774-F, Volvo VCS	
Suitable for	Porsche	
Density at 20 °C	1037 kg/m ³	EN ISO 12185
Գույն	Violet	տեսողական
pH - value at 20 °C	7,0 - 8,0	ASTM D1287
Սառեցման կետ	-15 °C	ASTM D1177

Out of production

Product	Vendor	Barcode
10 l	1410113-010-01-999	
60 l	1410113-060-01-995	
208 l	1410113-208-01-995	